

Liquid-Tight Flexible Steel Conduit

Features:

- The inside surface is made galvanized steel, the outside part is PVC coated.
- Considering heavy duty service conditions it is recommended to use it with B.. type connectors.
- There is a cord inserted in the conduit in order to increase its bending durability.
- Operating Temperature -40°C / +120°C (BLACK-GRAY)



MSM Code BLACK	MSM Code GREY	Size	Inside Diameter (mm)	Outside Diameter (mm)	Standard Meter Per Piece
MLY-10	MLY-10.G	1/4"	10,0	14,0	30
MLY-13	MLY-13.G	3/8"	13,0	17,0	30
MLY-16	MLY-16.G	1/2"	16,0	21,0	30
MLY-21	MLY-21.G	3/4"	21,0	26,0	30
MLY-26	MLY-26.G	1"	26,0	32,0	30
MLY-35	MLY-35.G	1 1/4"	35,0	41,0	15
MLY-40	MLY-40.G	1 1/2"	40,0	47,0	15
MLY-52	MLY-52.G	2"	52,0	59,0	15
MLY-63	MLY-63.G	2 1/2"	63,0	72,0	15
MLY-78	MLY-78.G	3"	78,0	88,0	7,5
MLY-102	MLY-102.G	4"	102,0	112,0	7,5

Note: ±5% tolerance of above-mentioned physical characteristics.

Applications:

- Due to its acid, oil and water resistance it is especially used in construction of industrial facilities, suitable for outside use.